

# COMPRESSORS



## PORTABLE CONTRACTOR SERIES COMPRESSORS – OIL LUBE, DIRECT DRIVE

- For professional, farm, home and hobbyists
- Quiet running and low 1720 RPM pump
- Die cast aluminum pump with cast iron sleeves and stainless steel valves for longer life
- All electrical units draw 15 amps or under
- Manual reset for overload protection
- Includes: Regulator, pressure gauge, pressure switch with on/off, universal coupler, filter silencer with replacement element and pump oil
- Air outlet accepts 1/4" industrial male quick connector
- Factory tested prior to shipment
- Not intended for commercial use
- CSA approved
- 1-year limited manufacturer's warranty



TFA008



TFA009



TFA010



Model No.	Mfg. No.	Peak HP	Running HP @ 90 PSI	Actual FAD-CFM 90 PSI	Actual FAD-CFM 125 PSI	Voltage /Phase	Amp Draw @ 125 PSI	Tank Size (gal.)	Pump RPM	Dimensions L" x W" x H"	Wt. lbs.	Price /Each
TFA008	DD-1004	1	1	4.5	4	115 V/1 PH	15	4	1720	16 x 16 x 23	65	
TFA009	DD-1503	1.5	1.5	6	4.6	115 V/1 PH	14	3.2	1720	22 x 9 x 23	55	
TFA010	DD-2022B	2	1.5	6	4.6	115 V/1 PH	15	4	1720	21 x 20 x 20	80	

## KING CANADA INDUSTRIAL COMPRESSORS

- 2-cylinder cast iron single stage oil lubricated pump
- ASME registered tank and safety valve
- Large intake filters
- Pump with V-style design minimizes vibration, improves cooling and extends compressor life
- Portable units are equipped with 9 1/2" pneumatics wheels and front handle
- Gas units are equipped with a 4-stroke air cooled OHV Honda gas engine



TLV740



TLV742



TLV743



TLV744

TLV739



TLV741



Model No.	Mfg. No.	Peak HP	Air Delivery CFM 40 PSI	Air Delivery CFM 90 PSI	Max. PSI	Voltage/Phase	Tank Size (gal.)	Amp Draw Motor	Pump RPM	Wt. lbs.	Remarks	Price /Each
TLV739	KC-2051H1	5.5	7.6	6.0	150	120 V/1 PH	20	15	3450	145	Horizontal	
TLV740	KC-3124v1	5.5	7.6	6.0	150	120 V/1 PH	24	15/7.5	3600	170	Vertical	
TLV742	KC-6160v1	6.5	13.4	11.2	150	208/240 V/1 PH	60	15	3450	260	Vertical	
TLV743	KC-5160V1	6.5	22.6	18.5	150	208/240 V/1 PH	60	23	3450	280	Vertical	
TLV744	KC-7180V1-MS	7.5	43.0	30.0	150	208/240 V/1 PH	80	33	1800	510	Vertical	
TLV741*	KC-5510G1	5.5	14.1	11.2	150	5.5 HP Gas	10(2x5)	N/A	3600	165	Twin Horizontal	

\*Gas powered