

CHAIN HOISTS

- · Lightweight steel construction
- Triple spur geared for easy lifting
- Load brake assures safety and load control
- High tensile alloy steel load chain for increased strength and durability
- Latched swivel hooks for added security
- Enclosed chain guide ensures dirt and dust do not affect operation
- Meets ASME B30.16

KLETON

Model No.	Lift'	Cap lbs.	Wt. lbs.	Price/Each
LS534	10	1000	24	
LS535	10	2000	29	
LS536	10	3000	44	
LS537	10	4000	48	
LS538	10	6000	59	
LS539	10	10 000	100	
LS540	20	1000	36	
LS541	20	2000	40	
LS542	20	3000	59	
LS543	20	4000	62	
LS544	20	6000	84	
LS545	20	10 000	136	



LEVER HOISTS

- · Lightweight steel construction
- Short steel handle rotates 360° to allow operation in any position
- Load brake assures safety and load control
- High tensile alloy steel load chain for increased strength and durability
- Latched swivel hooks for added security
- Enclosed chain guide ensures dirt and dust do not affect operation
- Meets ASME B30.16



Model No.	Lift'	Cap lbs.	Wt.lbs.	Price/Each
LS546	5	1500	15	
LS547	5	2000	18	
LS548	5	3000	24	
LS549	5	6000	42	
LS550	5	12 000	62	



ADJUSTABLE TROLLEYS

- Easily adjusts to fit various flanges, I-beams and H-beams
- Use on straight or curved track
- Can be installed or removed at any position on the beam
- Heavy-duty cast iron wheels
- Deep width flange provides superior contact with the beam
- Geared trolleys include two geared wheels operated by hand chain
- Safety plate included
- Meets ASME B30.16



Model No.	Fits I beams"	Cap. Ibs.	Wt. Ibs.	Price /Each
PLAIN				
LS551	2 11/16 - 5 3/8	1000	10	
LS552	3 1/8 - 6 1/4	2000	17	
LS553	3 1/8 - 6 1/4	4000	28	
LS554	3 7/16 - 7 3/8	6000	46	
LS555	4 13/16 - 9 9/16	10 000	73	
GEARED)			
LS556	2 11/16 - 5 1/4	1000	18	
LS557	3 1/8 - 5 15/16	2000	25	
LS558	3 1/8 - 7 1/16	4000	36	
LS559	3 7/16 - 7 3/8	6000	54	
15560	43/4-73/4	10 000	81	

Adjustable Plain Trolley





MANUAL CHAIN HOISTS

- · Simple, efficient, economical design
- Equipped with hardened load chain for flexibility and long wear
- Compact design, low headroom and lightweight steel construction for easy installation, even in confined spaces
- Brake requires no lubrication
- Forged swivel hooks with latches reduce twisting of chain and unintentional unhooking of load when chain is slack
- Standard hand chain drop is 2' less than lift

Model No.	Lift'	Cap. Tons	Wt. lbs.	Price/Each
QG621	10	1/2	18	
Q1069	10	2	61	
LS935	10	3	89	
LS937	10	5	91	
LS930	20	1/2	30	
LS932	20	1	38	
LS934	20	2	80	
LS936	20	3	109	
LS938	20	5	123	

Note: Additional lifts & capacities available on request



CBT ADJUSTABLE TROLLEYS

- Adjustable trolleys are available in plain and geared to fit most applications up to 8.7" beam flange widths
- Dual tread wheels will fit either tapered or flat beam flanges and include permanently lubricated, shielded ball bearings for long life and reduced maintenance

• Lifetime warranty						
Model	Stand Beam	Stand Beam	Wt.	Capacity		Price
No.	Height"	Width"	lbs.	Tons	lbs.	/Each
PLAIN						
LT296	4-24	2.0-8.7	19	1/2	1000	
LT297	5-24	2.3-8.7	26	1	2000	
LT299	6-24	2.3-8.7	46	2	4000	
LT300	8-24	3.0-8.7	86	3	6000	
LT301	10-24	3.5-8.7	130	5	10 000	
GEARE	:D					
LT302	5-24	2.3-8.7	26	1	2000	
LT304	6-24	2.3-8.7	46	2	4000	
LT305	8-24	3.0-8.7	86	3	6000	
LT306	10-24	3.5-8.7	130	5	10 000	





LEVER HOISTS

SERIES 602 & 603 MINI RATCHET

The Series 602 mini hoist is the most compact ratchet lever hoist in the market

- Use in confined conditions with one hand operation
- Free chaining feature serves to quickly attach the load
- Impact resistant all-steel frame, gear case and cover

Model No.	Lift'	Capacity lbs.	Weight lbs.	Price /Each
LS706	5	550	6	
LS707	5	1100	7	
LT591	10	550	7	
LT592	10	1100	8	



SERIES 640 PULLER

The Series 640 long handle puller is ideal for a broad range of pulling applications

- Easy one-hand operation
- Free chaining for fast, easy attachment to load
- Tough yet lightweight aluminum construction and powder coat finish
- Lifetime warranty

Model No.	Lift'	Capacity lbs.	Weight lbs.	Pric /Eac
LS724	5	1500	17	
LS725	5	3000	26	
LS726	5	6000	38	
LS727	5	12000	73	

