DOCK EQUIPMENT

SLOWSTOP® FLEXIBLE REBOUNDING BOLLARD

- Protect buildings, assets, vehicles, and pedestrians from damaging collisions with this incredibly strong surface mounted bollard that absorbs energy from impacts then rebounds back to its original position without damage
- Includes all necessary installation pieces
 60µm hot-dipped galvanized & 60µm
- polyester outdoor powder coatings

4" DIAMETER BOLLARDS

- Ideal for medium applications such as cars, light trucks, and typical fork lifts
- Stops 5000 pounds at 3.4 mph without damage

6" DIAMETER BOLLARDS

- Perfect for heavy applications such as delivery trucks, heavy fork lifts, and even semi-trailers
- Stops 5000 pounds at 7.5 mph without damage

DRILLED BOLLARDS

• Features mounting holes and plugs that can be used to attach guardrails

Model	Mfg.				Price
No.	No.	Туре	Dia."	Height"	/Each
MP184	60-5201-A	Standard	4	42	
MP185	60-5203-A	Standard	6	42	
MP186	60-5261-A	Drilled	4	42	
MP187	60-5263-A	Drilled	6	42	

PROGUARDS TEMPORARY GUARD RAIL POSTS

- Allows you to quickly and easily create fully compliant guardrails that provide the required fall protection from the unsafe areas of the job site
- Connect 2x4 rails to the supplied posts
 Dual hooks allow for 90° installs and
- angled stair rails and handrails
- Width: 8"
 Height: 39
- Height: 39"
 Calaury Orange
- Colour: Orange
 Orange
- Qty/Box: 2 PostsHook Height: 3.5"
- Hook Height: 3.5
 Hook Depth: 1.5"
- No. of Screw Holes: 8

Model No. MP191 Mfg. No. 70-8010

Price/Each \$



SPRING LOADED BOLLARD

- Designed to serve as a visual warning to personnel
- 30° spring-loaded design will bend and
- not break like rigid bollards Overall Length: 2-1/8"
- Overall Length: 2-1/8
 Overall Width: 2-1/8
- Overall Height: 42"
- Colour: Yellow
- Material: Steel

Model No. MP197 Mfg. No. SPBOL-42

Price/Each \$





Can't find what you're looking for? Call us today!

SLOWSTOP® FLEXRAIL GUARD RAIL

- Mount to SlowStop® Rebounding Bollards for immediate and second se
- increased strength and system durability Overall Height: 13-3/4"
- Material: Polycarbonate
- Break Strength: 24832 lbf / 110 kN
- Maximum Deflection: 21"/ 56 cm

END CAPS

- Attaches to sections of SlowStop[®] FlexRail to provide an end impact zone in the most likely direction of travel
- Female: Attaches to recessed side of FlexRail guard rail
- Male: Attaches to straight ends of FlexRail guard rail



MP189 MP190 Mode Mfg. **Overall** Price No. No. Туре Length /Each MP188 60-5250 Rail 157-1/2 MP189 60-5256 End Cap - Female 9-4/5 MP190 60-5257 End Cap – Male 9-4/5

MP186

MP185