

CORDED GRINDERS & SANDERS

HIGH PERFORMANCE 6" GRINDER WITH SLIDE SWITCH

- Power Loss Reset® prevents accidental restarts following a power disruption when the tool is left in the "on" position
- Dust ejection system provides durability by ejecting damaging dust and debris particles that enter through the air intake vents
- E-Clutch™ activates in less than a tenth of a second when a pinch/stall is detected, shutting down the motor
- Includes: Side handle, inner and outer flange, 6" type 27 guard, 6" type 1 guard
- Power Tool Type: Corded

Model No. TYW993
Mfg. No. DWE43140
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 6"
Voltage: 120 V
Amperage: 13.0
Max. Watts Out: 1700 W
No Load RPM: 9000
Spindle Size: 5/8" - 11
Tool Weight: 6.2 lbs.

6" ANGLE GRINDER

- Trigger Switch with No Lock-On Button
- SJS (Super Joint System) prevents kickback during wheel lock
- Electric Brake for increased operator safety
- Rotatable gear housing can be positioned at every 90° for optimal positioning
- Removable side handle can be mounted on left or right side of tool
- Ergonomic soft rubber grip design for vibration absorption and comfortable operation
- Includes: Grip, Lock Nut Wrench, Tool-less Wheel Cover, 6" Depressed Centre Wheel, Inner Flange, Lock Nut, Dust Cover Attachment

Model No. TNB127
Mfg. No. GA6020
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 6"
Voltage: 120 V
Amperage: 10.5
No Load RPM: 10 000
Spindle Size: 5/8" - 11 UNC
Tool Weight: 6.6 lbs.

ANGLE GRINDERS

- Ergonomic soft rubber grip for vibration absorption and comfortable operation
- Removable side handle can be mounted on left or right side of tool
- Rotatable gear housing can be positioned at every 90°
- Rear handle swivels 180°
- Includes: Vibration proof grip, dust cover attachment set, lock nut wrench, toolless wheel cover assembly, inner flange and lock nut

Model No. TLV144
Mfg. No. GA7031
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 7"
Voltage: 120 V
Amperage: 15.0
No Load RPM: 8500
Spindle Size: 5/8"
Tool Weight: 13.5 lbs.

ANGLE GRINDERS

- Labyrinth construction seals motor and bearings from contamination
- Removable side handle can be mounted in three positions
- Low vibration rear handle with soft grip for operator comfort and control
- Includes: 7" depressed centre wheel and side handle

Model No. TLY386
Mfg. No. GA7020
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 7"
Voltage: 120 V
Amperage: 15.0
No Load RPM: 8500
Spindle Size: 5/8"
Tool Weight: 11.2 lbs.

HEAVY-DUTY BIG 6™ GRINDER

- Built-in temperature sensor protects motor from burnout
- Built-in safety feature prevents accidentally restarting after a power failure
- Soft start feature reduces peak power loads and torque at start-up
- Includes: Side handle, flange, quick nut and wheel guard

Model No. TD923
Mfg. No. 30A260
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 6"
Voltage: 120 V
Amperage: 14.5
No Load RPM: 9600
Spindle Size: 5/8" - 11
Tool Weight: 5.9 lbs.



MAXI GRINDER™ 7"

- Carbon brush service door
- Lower profile gear housing
- More powerful motor, improved DUSTGUARD protection
- New ergonomic design with rotating back handle
- Tool-free adjustable guard and spindle lock

Model No. TD924
Mfg. No. 30A170
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 7"
Voltage: 120 V
Amperage: 15.0
No Load RPM: 8500
Spindle Size: 5/8" - 11
Tool Weight: 12.8 lbs.



MAXI GRINDER™ 9"

- Carbon brush service door
- Lower profile gear housing
- More powerful motor, improved DUSTGUARD protection
- New ergonomic design with rotating back handle
- Tool-free adjustable guard and spindle lock

Model No. TD925
Mfg. No. 30A190
Price/Each \$



SPECIFICATIONS

Wheel Diameter: 9"
Voltage: 120 V
No Load RPM: 6000
Spindle Size: 5/8" - 11
Tool Weight: 12.8 lbs.

