MEASURES, RULES, SQUARES & LEVELS

RED BEAM SELF-LEVELING HORIZONTAL & VERTICAL ROTARY LASER

- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically
- Laser beam modes include dot, two adjustable line lengths and two rotational speeds Includes: 1 Rotary Laser, 1 Remote Control, 1 Detector with Clamp, 1 Tinted
- Glasses, 1 Target, 1 Multi-Function Mount, 1 NiMH rechargeable battery pack, 1 6.4V battery adapter, 1 Alkaline battery compartment (batteries not included), 1 Hard-Shell Carrying Case, 1 Instruction Manual

I JOHNSON



TECHNICAL SPECIFICATIONS

| Model No. | IB940 |
|----------------------|--|
| Mfg. No. | 40-6534 |
| Laser Wave Length: | 635 Nm |
| Laser Class: | Class 111 |
| Accuracy: | ±1/8"/100 ft. |
| Interior Range: | Up to 200 ft. diameter depending upon light conditions |
| Exterior Range: | Up to 1500 ft. diameter with detector |
| Remote Range: | Up to 200 ft. diameter |
| Power Supply: | NiMH rechargeable battery pack and 6.4V adapter included |
| Working Temperature: | 14°F-113°F |
| Scanning Modes: | 0°, 30°, 60° |
| Rotational Speeds: | 200 and 500 RPM |
| Price/Each | \$ |

INTERIOR & EXTERIOR ROTARY LASER LEVEL KITS

- · Horizontal self-leveling automatically aligns the laser to centre
- Protected rotary head and weatherproof design deliver
- interior and exterior jobsite durability Standby mode allows the user to pause the laser while
- transitioning from horizontal to vertical Equipped with leveling vial for manual leveling in vertical mode
- Includes: (2) D batteries, (1) Detector and clamp, (1) Wall mount, (1) Target card, (1) Contractor's bag, (1) 9-Volt battery



TECHNICAL SPECIFICATIONS

Model No. Mfg. No. Laser Beam Colour: Laser Wave Length: Laser Class: Accuracy per 100': **Interior Range:** Range with Detector: **Rotation Speeds:** Self-Leveling Range: Price/Each

TLY375 DW074KD Red 635 Nm Class IIIA 1/4" 100' 600' 0, 60, 600 RPM ±5° \$

GREEN BEAM SELF-LEVELING HORIZONTAL & VERTICAL ROTARY LASER

- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically
- Laser beam modes include dot, two adjustable line lengths and two rotational speeds
- Includes: 1 Rotary Laser, 1 Remote Control, 1 Detector with Clamp, 1 Tinted Glasses, 1 Target, 1 Multi-Function Mount, 1 NiMH rechargeable battery pack, 1 6.4V battery adapter, 1 Alkaline battery compartment (batteries not included), 1 Hard-Shell Carrying Case, 1 Instruction Manual

I JOHNSON



TECHNICAL SPECIFICATIONS

| Model No. | IB941 |
|----------------------|--|
| Mfg. No. | 40-6544 |
| Laser Wave Length: | 532 Nm |
| Laser Class: | Class 111 |
| Accuracy: | +/-1/8"/100 ft. |
| Interior Range: | Up to 400 ft. diameter depending upon light conditions |
| Exterior Range: | Up to 1200 ft. diameter with detector (not included) |
| Remote Range: | Up to 200 ft. diameter |
| Power Supply: | NiMH rechargeable battery pack and 6.4V adapter (included) |
| Working Temperature: | 32°F-104°F |
| Scanning Modes: | 0°, 30°, 60° |
| Rotational speeds: | 200 and 500 RPM |
| Price/Each | \$ |

3 BEAM SELF-LEVELING LINE LASER

- 3 Beam Line Laser to aid in 90° layout
- 2x Brighter diode to increase visibility in bright job site conditions
- Built-in magnetic pivot bracket mounts easily on metal surfaces
- 1-button operation and control panel for ease of use
- Micro adjust knob for precise alignment of 90° intersecting lines over greater distances
- Includes: 4 AA batteries for 30 hours of run-time, Ceiling Mount and Kit Box





TECHNICAL SPECIFICATIONS Model No. Mfg. No. Accuracy: Power:

Run Time:

Price/Each

TMB038 DW089K ±1/8"@30' 6 V, 4-AA Battery 30 hours Ś

TOOLS & EQUIPMENT