

# CHEMICALS

## SPOTCHECK® AEROSOLS

### SKL-SP1 SPOTCHECK® PENETRANT

- Post emulsifiable penetrant
- Most widely used, general purpose
- Solvent removable

### SKD-S2 SPOTCHECK® DEVELOPER

- Non-chlorinated solvent developer
- Meets major requirements for special alloy and nuclear applications

### SKC-S SPOTCHECK® CLEANER

- Non-chlorinated cleaner/remover
- Recommended general purpose
- Meets major requirements for special alloy and nuclear applications



MAGNAFLUX®

Model No.	Mfg. No.	Description	Price /Each
NP701	01-5149-68	SKL-SP1 Penetrant	
NP702	01-5352-68	SKD-S2 Developer	
NP703	01-5750-68	SKC-S Cleaner	

## FORM-A-THREAD®

### STRIPPED THREAD REPAIR KIT

- Permanently repairs stripped threads and fasteners in 5 minutes
- Allows up to 128 lbs. of torque
- Operating temperature between -65°F & 300°F
- Accepted for use in Canadian food processing facilities



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA458	236382	4.8 ml	

## PIPE REPAIR KITS

- Urethane impregnated fiberglass tape, activated by water, for reliable, temporary repairs of metal, plastic, and composite pipes
- Cures in 30 minutes
- Includes: Loctite® Fixmaster® Metal Magic Steel™ epoxy stick, urethane impregnated fiberglass tape, and gloves
- Accepted for use in Canadian food processing facilities



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA641	209818	2" x 6' tape	

## FIXMASTER® STEEL PUTTY

- Steel filled, non-sagging, two-part epoxy that cures to a metal-like finish for rebuilding or repairing metal parts
- 0.3 sq.ft. coverage, at 1/4" thickness
- 225°F maximum operating temperature
- 4900 PSI tensile strength
- 30 minutes working time
- Functional cure in 6 hours
- Accepted for use in Canadian food processing facilities
- Colour: Grey



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AC341	219292	1 lb. kit	

## FIXMASTER® ALUMINUM PUTTY

- Rebuilds and repairs aluminum equipment, forming a non-rusting finish
- 0.5 sq.ft. coverage, at 1/4" thickness
- 225°F maximum operating temperature
- 4000 PSI tensile strength
- 20 minutes working time
- Functional cure in 6 hours
- Accepted for use in Canadian food processing facilities
- Colour: Aluminum



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AC334	235615	1 lb. kit	

## FIXMASTER® STAINLESS STEEL PUTTY

- Forms a non-rusting, very hard, durable finish on damaged stainless steel surfaces
- 0.25 sq.ft. coverage, at 1/4" thickness
- 225°F maximum operating temperature
- 4600 PSI tensile strength
- 20 minutes working time
- Functional cure in 6 hours
- Accepted for use in Canadian food processing facilities
- Colour: Grey



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AC332	235613	1 lb. kit	

Ask us about volume prices!

In many cases you will benefit from quantity prices.

