

LIGHT INDUSTRIAL DIRECT DRIVE DRUM FANS

- 120 V/60 Hz, 2-speed motor
- All-metal construction, painted black
- 6' SJT power cord
- 6" casters and easy moving handle



Model No.	Blade size"	HP	Watts	CFM		Wt. lbs.	Price /Each
				High	Low		
EA286	28	2/5	290	8050	6650	22	
EA288	36	3/5	405	11200	9100	30.5	

42" BELT DRIVE DRUM FANS

- 115 V, 1 HP, 2-speed, 1-phase, ball bearing motor
- Motor out of air stream – stays clean
- Aluminum 4-bladed propellers
- Rocker switch
- Epoxy coated steel spiral, resilient mount guards
- Steel hubbed wheels, swivel locking casters
- 20-gauge roll form epoxy coated housing
- 10' three-conductor cord and plug
- CFM: 17 100 (high), 9558 (low)
- RPM: 430 (high), 285 (low)
- Quiet operation: 75 dB (high), 67 dB (low)
- Weight: 130 lbs.



Model No. EA319
Price/Each \$



2-YEAR WARRANTY

DIRECT DRIVE 4-IN-1® DRUM FANS

- 115 V, 1 phase, ball bearing motor
- One fan with four mounting options in the same carton: Hanging mount, ceiling mount, wall mount, portable barrel
- Guards, barrel mountings epoxy coated
- Pull chain switch
- Tilttable



2-YEAR WARRANTY



Model No.	Blade Size"	HP	# of Speeds	CFM			RPM			Wt. lbs.	Price /Each
				High	Med	Low	High	Med	Low		
EA336	30	1/4	3	5670	4590	3410	1110	810	600	97	
EA337	36	1/2	2	11200	-	8090	830	-	600	119	

INDUSTRIAL WORKSTATION FANS

- 120 V/60 Hz enclosed motor
- Features 1.8 m power cord with UL/CUL plug
- Locking arm sold separately

180° DOUBLE LOCKING ARM WITH 2 RECEPTACLES

- Moveable arm to accommodate many locations, applications and positions
- Wide range of motion - will not sag when extended
- 2 AC receptacles for easy fan hook-up



Model No.	Blade Size"	Blade Material	HP	No. of Speeds	CFM	Price /Each
EB540	12	Aluminum	1/12	3	2600/2400/1600	
EB541	18	Aluminum	1/4	3	3800/3600/2600	
EB542	24	Aluminum	1/3	2	8600/5900	
EB539	180° Double Locking Arm with 2 Receptacles					

